INTERCOM SPECS

WHOO.AI MOBILE VIDEO INTERCOM

WWW.WHOO.AI

2025
2026

ALL YOU NEED TO KNOW

PHYSICAL&POWER

Size:12.75x5.11x1.1 inches (HxWxD)
Body material: Aluminum
RAM / ROM: 2GB / 16GB
Display: 7” IPS LCD
Screen: 7” capacitive touch screen
Camera: 3 Megapixels, automatic lighting
Relay In/Out: 3/3
Installation: On-wall or In-wall
Water-proof & Dust-proof: IP65

VIDEO

Resolution: up to 1080p
Maximum image transfer rate: 1080p - 30fps
High intensity LEDs for picture lighting during dark hours

NETWORKING

10/100 Mbps Ethernet connection
DHCP Client or Static IP
Network-Time-Protocol

DOOR ENTRY FEATURE

Internal DPDT relay for controlling a door opener
Relays controlled individually by DTMF tones or messages
Camera permanently operational, not just during calls
White balance: auto
Viewing angle: 120 °
Minimum illumination: 1LUX (without LED illumination)

MORE SPECS

Ethernet port: RJ45, 10/100Mbps adaptive
802.3af Power-over-Ethernet
12V DC connector (if not using PoE)
IP/IK Level: IP65/ IK06
Installation: Flush-mounted & Wallmounted
Flush-mounted DIM: 324x130x60mm
Wall-mounted DIM: 324x130x33mm
Working Humidity: 10-90%
Working Temperature: -20°C - +55°C
Storage Temperature: -40°C - +70°C

GET IN TOUCH

REAL STATE AND BUILDINGS

WWW.WHOO.AI
+1 (229) 4666950
60 POWELL STREET #1 BROOKLINE, MA